



Donaldson®

85 Railroad Drive
 Ivyland, PA 18974 USA
 Tel (215) 396-8349
 Fax (215) 396-8308
<http://www.tetratex.com>

DONALDSON MEMBRANE PRODUCT REFERENCE GUIDE

	PRODUCT CODE	DESCRIPTION	WIDTH
Low Temperature Felts	5212-83	15.5 oz. Fiber Supported Polyester	83"
	6202-83	13 oz. Polyester Felt	83"
	6212-83	16 oz. Polyester Felt - Standard Efficiency	83"
	6222-83	15 oz. Polypropylene Felt	83"
	6235-83	15 oz. Homopolymer Acrylic Felt	83"
	6272-83	14 oz. Polyester Epiropic Felt	83"
	8005-83	16 oz. Polyester Felt - High Efficiency	83"
	8006-83	15 oz. Polyester Felt	83"
	8135-83	15 oz. Homopolymer Acrylic Felt – High Efficiency	83"
	8212-83	16 oz. Polyester Felt with Tetratex 2	83"
High Temperature Felts	5244-83	14 oz. Aramid Felt Fiber Supported Polyester	83"
	5263-83	17 oz. PPS Fiber Supported	83"
	6232-83	14 oz. P-84® Felt	83"
	6262-83	16 oz. Ryton® Felt	83"
	6242-83	14 oz. Nomex® Felt	83"
	6243-83	14 oz. Acid Resistant Nomex® Felt	83"
	6244-83	14 oz. Aramid Felt	83"
	8144-83	14 oz. Aramid Felt – High Efficiency	83"
	8162-83	16 oz. PPS Felt – High Efficiency	83"
	8244-83	14 oz. Aramid with Tetratex 2	83"
Woven Synthetics	6281-54	9 oz. Woven Ryton® Fabric	54"
	6285-54	10 oz. Woven Nomex® Fabric	54"
	6288-54	9 oz. Woven Polyester High Efficiency	54"
	7001-54	7 oz. Woven Homopolymer Acrylic	54"
	7008-54	9 oz. Woven PTFE	54"
	7009-54	6 oz. Woven Polyester High Efficiency	54"
	7010-54	6 oz. Woven Polyester Stainless Steel	54"
	7012-65	20 oz. Woven PTFE	65"
Woven Fiberglass	6252-65	16 oz. Woven Fiberglass	65"
	6253-38.5	14 oz. Woven Fiberglass	38.5"
	6254-38.5	10 oz. Woven Fiberglass	38.5"
	6255-54	22 oz. Woven Fiberglass	54"
	7002-38.5	10 oz. Acid Resistant Woven Fiberglass	38.5"
	7003-38.5	14 oz. Acid Resistant Woven Fiberglass	38.5"
	7005-65	22 oz. Acid Resistant Woven Fiberglass	65"